

Your source for high quality, affordable lasers

## **DATA SHEET**

## HIGH POWER BLUE DIODE LASER **AT 447nm**

Diode laser module at 447nm is made features of round spot, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.













## Model: MDL-W-447/8W~20W

Wavelength ( nm )		447 ±5		
Output Power ( W )	>8	>10, 12	>20	
Operating Mode		CW		
Power stability (rms, over 4 hours)		<1%, <3%, <5%		
Warm-up time (minutes)		<5		
Beam divergence, full angle (mrad)		<2.0×0.5		
Dimensions of beam at the aperture (mm)	6×5	11×5	11×10	
Beam height from base plate (mm)		93.5		
Operating temperature ( $^{\circ}$ C)		10~35		
Power supply (90-264VAC)		PSU-W-FDA		
Modulation option	TTL/Analog 1Hz-5K	TTL/Analog 1Hz-5KHz, 1Hz-10KHz, 1Hz-30KHz, and TTL		
	on/off			
Expected lifetime (hours)		10,000		
Warranty period		1 year		

## **MDL-W-447 Dimensions PSU-W-FDA Dimensions DPSSL DRIVER** 0 ..... $307 \text{ (L)} \times 168 \text{ (W)} \times 123 \text{ (H)} \text{ mm}^3, 5.1 \text{kg}$ $305(L) \times 164(W) \times 131(H) \text{ mm}^3$ , 8.4kg