



Your source for high quality, affordable lasers

DATA SHEET

LD PUMPED ALL-SOLID-STATE YELLOW LASER AT 593.5nm

All solid state 593.5nm yellow lasers is made features of ultra-compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, etc.

Model: MGL-F-593.5/50~150mW

Wavelength (nm)	593.5 ± 1nm		
Output power (mW)	>50, 100, 150		
Transverse mode	TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<3%, <5%, <10%		
Warm-up time (minutes)	<10		
M ² factor	<1.5		
Beam divergence, full angle (mrad)	<2.0		
Beam diameter at the aperture (1/e ² , mm)	~3.0		
Beam height from base plate (mm)	45		
Polarization ratio	>100:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA	PSU-H-OEM
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option		
Expected lifetime (hours)	10,000		
Warranty period	1 year		



MGL-F-593.5	PSU-H-LED	PSU-H-FDA	PSU-H-OEM
<p>211(L) × 88(W) × 74(H) mm³, 1.6kg</p>	<p>277 (L) × 145(W) × 106 (H) mm³, 2.6 kg</p>	<p>275 (L) × 145(W) × 104 (H) mm³, 2.3kg</p>	<p>245.5 (L) × 146(W) × 94 (H) mm³, 2.2kg</p>

<http://www.ultralasers.com>

Ultralasers, Inc.

Tel : +1-647-800-0936 ;

Fax : +1-647-340-7118

Email : sales@ultralasers.com