




DATA SHEET

LD PUMPED LL-SOLID-STATE Q-SWITCHED LASER AT 526.5nm

All solid state 526.5nm Q-switched laser has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in medical, scientific research, industry, etc.



Wavelength (nm)		526.5 ± 1nm
Operating mode		Q-switched pulsed laser
Single pulse energy (μJ)		1 ~ 10
Pulse duration (ns)		~15
Peak power (W)		~700
Rep. rate (kHz)	Controllable	Specified One rep. rate, such as 1k, 2k, 3k, up to 4kHz, with stable laser pulses emitting (stable pulse energy, peak, duration and period). Different rep. rate in the range of 1Hz-4kHz can be obtained by input an external TTL signal.
	Uncontrollable	Undefined rep. rate among 4k-5kHz and unstable laser pulse emitting. Suitable for the applications only needs high peak power pulses.
Average power (mW)		Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)
Ave power stability (over 4 hours)		<3%, <5%
Transverse mode		TEM ₀₀
Warm-up time (minutes)		<10
M ² factor		<1.2
Beam divergence, full angle (mrad)		<1.5
Beam diameter at 1/e ² (mm)		~1.2
Beam height from base plate (mm)		24.8
Operating temperature (°C)		10~35
Power supply (90-264VAC)		PSU-III-FDA
Expected lifetime (hours)		10,000
Warranty period		1 year

MxL-III-526.5	Dimensions	PSU-III-FDA	Dimensions
 <p>140.8(L) ×73(W) ×46.2(H) mm³, 0.6kg</p>		 <p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>	