

MSL-U-532-S/1~800mW



**SINGLE LONGITUDINAL MODE
LASER AT 532nm**

All solid state single longitudinal mode laser is made features of ultra-compact, long lifetime, low cost and easy operating, which is used in DNA sequencing, flow cytometry, cell sorting, optical instrument, spectrum analysis, interference, measurement, holography, physics experiment, etc



SPECIFICATIONS

Wavelength (nm)	532±1
Operating mode	CW
Output power (mW)	1 - 800
Power stability (rms, over 4 hours)	<2%, <3%, <5%
Transverse mode	TEM ₀₀
Longitudinal mode	Single
Spectral linewidth (nm)	<0.00001
Coherent length (m)	>50
Noise of amplitude (rms, 1Hz~20MHz)	<0.5%, <1%
M ² factor	<1.2
Beam diameter at the aperture (1/e ² , mm)	<1.0
Beam divergence, full angle (mrad)	<1.5
Polarization ratio	>100:1, Vertical±5 degree (Horizontal Optional)
Warm-up time (minutes)	<5
Pointing stability after warm-up (mrad)	<0.05
Beam height from base plate (mm)	27.4
Operating temperature (°C)	10~40
Laser head consumption(W)	15 (typical), <25 (40°C)
Power supply (90-264VAC)	PSU-H-FDA
Expected lifetime (hours)	10000
Warranty	1 year



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MSL-U-532	PSU-H-FDA
<p>142.5(L)×60(W)×50(H) mm³, 1.0 kg</p>	<p>275(L)×145(W)×104(H) mm³, 2.3 kg</p>